

4.11 NOISE AND VIBRATION

This section provides a description of the existing ambient noise environment for the project area and describes applicable federal, state, and local regulations (Section 4.11.1). Potential noise or vibration impacts associated with the project-related facilities, as described in Chapter 3.0, Project Description, are considered in Section 4.11.2 and, if necessary, mitigation is proposed based on the anticipated level of significance. Section 4.11.3 concludes by describing significant residential impacts following the application of mitigation, if any.

4.11.1 Environmental Setting

Noise is defined as unwanted sound. Pressure waves traveling through air exert a force registered by the human ear as sound. Sound, traveling in the form of waves from a source, exerts a sound pressure level (referred to as sound level), which is measured in decibels (dB), with zero dB corresponding roughly to the threshold of human hearing and 120 to 140 dB corresponding to the threshold of pain.

The typical human ear is not equally sensitive to all frequencies of the audible sound spectrum. Consequently, when assessing potential noise impacts, sound is measured using an electronic filter that de-emphasizes the frequencies below 1,000 hertz (Hz) and above 5,000 Hz to imitate the human ear's decreased sensitivity to low and extremely high frequencies. This emulation of the human ear's frequency sensitivity is referred to as A-weighting and is expressed in units of A-weighted decibels (dBA). Frequency A weighting follows an international standard method of frequency de-emphasis and is typically applied to community noise measurements. In practice, the specific sound level from a source is measured using a meter incorporating an electrical filter corresponding to the A-weighting curve. All noise levels reported are A-weighted unless otherwise stated.

Noise Exposure and Community Noise

Community noise varies continuously over a period of time with respect to the sound sources contributing to the community noise environment. Community noise is primarily the product of many distant noise sources that constitute a relatively stable background noise exposure, with the individual contributors unidentifiable. The background noise level changes throughout a typical day, but does so gradually, corresponding with the addition and subtraction of distant noise sources such as traffic and atmospheric conditions. Community noise is constantly changing throughout the day due to short duration single event noise sources, such as aircraft flyovers, vehicle passbys, and sirens. These successive additions of sound to the community noise environment vary the community noise level from instant to instant. This requires the measurement of noise exposure over a period of time to legitimately characterize a community noise environment and evaluate cumulative noise impacts. This time-varying characteristic of environmental noise is described using statistical noise descriptors. The most frequently used noise descriptors are summarized below (Caltrans 1998):

- L_{eq} : the equivalent sound level is used to describe noise over a specified period of time, typically one hour, in terms of a single numerical value. The L_{eq} is the constant sound level which would contain the same acoustic energy as the varying sound level, during the same time period (i.e., the average noise exposure level for the given time period).
- L_{max} : the instantaneous maximum noise level for a specified period of time.
- L_{dn} : 24-hour day and night A-weighted noise exposure level which accounts for the greater sensitivity of most people to nighttime noise by weighting noise levels at night ("penalizing" nighttime noises). Noise between 10:00 PM and 7:00 AM is weighted (penalized) by adding 10 dB to take into account the greater annoyance of nighttime noises. Similar to L_{dn} , Community Noise Equivalent Level (CNEL) adds a 5 dBA "penalty" for the evening hours between 7 PM and 10 PM in addition to a 10 dBA penalty between the hours of 10 PM and 7 AM.

Effects of Noise on People

The effects of noise on people can be placed in three categories:

1. Subjective effects of annoyance, nuisance, dissatisfaction;
2. Interference with activities such as speech, sleep, learning; and
3. Physiological effects such as hearing loss or sudden startling.

Environmental noise typically produces effects in the first two categories. Workers in industrial settings can experience noise in the last category. A satisfactory method for measuring the subjective effects of noise or the corresponding reactions of annoyance and dissatisfaction does not exist. However, a wide variation in individual thresholds of annoyance does exist, and different tolerances to noise tend to develop based on an individual's past experiences with noise.

Thus, an important way of predicting human reaction to a new noise environment is the way it compares to the existing environment to which one has adapted; i.e., the "ambient noise" level. In general, the more a new noise exceeds the previously existing ambient noise level, the less acceptable the new noise would be judged by those hearing it. With regard to increases in A-weighted noise level, the following relationships occur (Caltrans 1998):

- Except in carefully controlled laboratory experiments, a change of 1 dBA cannot be perceived;
- Outside of the laboratory, a 3 dBA change is considered a perceivable difference;
- A change in level of at least 5 dBA is required before any noticeable change in human response would be expected; and
- A 10 dBA change is subjectively heard as approximately a doubling in loudness, and can cause adverse response.

These relationships occur in part because of the logarithmic nature of sound and the decibel system. The human ear perceives sound in a nonlinear fashion hence the decibel scale was developed. Because the decibel scale is based on logarithms, two noise sources do not combine in a simple additive fashion, rather they combine logarithmically. For example, if two identical noise sources produce noise levels of 50 dB, the combined sound level would be 53 dB, not 100 dB. Because of this sound characteristic, if there are two noise emission sources, one producing a noise level greater than 9 dB than the other, the contribution of the quieter noise source is negligible and the sum of the noise sources is that of the louder noise source.

Noise Attenuation

Stationary point sources of noise, including stationary mobile sources such as idling vehicles, attenuate (lessen) at a rate between 6 dBA for hard sites and 7.5 dBA for soft sites for each doubling of distance from the reference measurement. Hard sites are those with a reflective surface between the source and the receiver such as parking lots or smooth bodies of water. No excess ground attenuation is assumed for hard sites and the changes in noise levels with distance (drop-off rate) is simply the geometric spreading of the noise from the source. Soft sites have an absorptive ground surface such as soft dirt, grass or scattered bushes and trees. In addition to geometric spreading, an excess ground attenuation value of 1.5 dBA (per doubling distance) is normally assumed for soft sites. Line sources (such as traffic noise from vehicles) attenuate at a rate between 3 dBA for hard sites and 4.5 dBA for soft sites for each doubling of distance from the reference measurement (Caltrans 1998).

The project area is characterized by an agricultural landscape and, therefore, soft surfaces are generally present throughout.

4.11.1.1 Regulatory Setting

This section presents federal, state, and local laws, plans, and regulations governing noise levels and allowable limits applicable to the projects.

Federal

Federal regulations establish noise limits for medium and heavy trucks (more than 4.5 tons, gross vehicle weight rating) under 40 Code of Federal Regulations (CFR), Part 205, Subpart B. The federal truck passby noise standard is 80 dB at 15 meters from the vehicle pathway centerline. These controls are implemented through regulatory controls on truck manufacturers. In addition to noise standards for individual vehicles, under regulations established by the U.S. Department of Transportation's Federal Highway Administration (FHWA), noise abatement must be considered for certain federal or federally-funded projects. Abatement is an issue for new highways or significant modification of an existing freeway. The agency must determine if the project would create a substantial increase in noise or if the predicted noise levels approach or exceed the Noise Abatement Criteria.

State

The state has also established noise insulation standards for new multi-family residential units, hotels, and motels that would be subject to relatively high levels of transportation-related noise. These requirements are collectively known as the California Noise Insulation Standards (California Code of Regulations, Title 24). The noise insulation standards set forth an interior standard of L_{dn} 45 dB for any habitable room. They also require an acoustical analysis demonstrating how dwelling units have been designed to meet this interior standard where such units are proposed in areas subject to noise levels greater than L_{dn} 60 dB. Title 24 standards are typically enforced by local jurisdictions through the building permit application process.

The State of California General Plan Guidelines, published by the Governor's Office of Planning and Research (OPR) in 1998, also provides guidance for the acceptability of projects within specific CNEL/ L_{dn} contours. The guidelines also present adjustment factors that may be used in order to arrive at noise acceptability standards that reflect the noise control goals of the community, the particular community's sensitivity to noise, and the community's assessment of the relative importance of noise pollution. The County of Imperial has utilized the adjustment factors provided and has modified the state's Land Use Compatibility standards for the purpose of implementing the Noise Element of its General Plan. Table 4.11-1 summarizes the acceptable and unacceptable community noise exposure limits for various land use categories as currently defined by the State of California. These community noise exposure limits are also incorporated into the County of Imperial General Plan Noise Element.

Local

County of Imperial General Plan

The County of Imperial General Plan Noise Element identifies and defines existing and future environmental noise levels from sources of noise within or adjacent to the County of Imperial; establishes goals and objectives to address noise impacts, and provides Implementation Programs to implement adopted goals and objectives. Table 4.11-2 summarizes the projects' consistency with the applicable General Plan noise policies. While this Environmental Impact Report (EIR) analyzes the projects' consistency with the General Plan pursuant to State California Environmental Quality Act (CEQA) Guidelines Section 15125(d), the Imperial County Board of Supervisors ultimately determines consistency with the General Plan.

Noise Impact Zones. A Noise Impact Zone is an area that is likely to be exposed to significant noise. The County of Imperial defines a Noise Impact Zone as an area which may be exposed to noise greater than 60 dB CNEL or 75 dB $L_{eq}(1)$.

TABLE 4.11-1. LAND USE COMPATIBILITY FOR COMMUNITY NOISE ENVIRONMENTS

Land Use Category	Community Noise Exposure – L _{dn} or CNEL (dBA)							
	50	55	60	65	70	75	80	
Residential	Blue			Green			Yellow	
	Blue			Green			Red	
Transient Lodging – Motel, Hotel	Blue			Green			Yellow	
	Blue			Green			Yellow	
Schools, Libraries, Churches, Hospitals, Nursing Homes	Blue			Green			Yellow	
	Blue			Green			Red	
Auditorium, Concert Hall, Amphitheaters	Green			Green			Yellow	
	Green			Green			Yellow	
Sports Arena, Outdoor Spectator Sports	Green			Green			Yellow	
	Green			Green			Yellow	
Playgrounds, Neighborhood Parks	Blue			Blue			Yellow	
	Blue			Blue			Red	
Golf Courses, Riding Stables, Water Recreation, Cemeteries	Blue			Blue			Yellow	
	Blue			Blue			Red	
Office Buildings, Business, Commercial and Professional	Blue			Green			Yellow	
	Blue			Green			Yellow	
Industrial, Manufacturing, Utilities, Agriculture	Blue			Blue			Green	
	Blue			Blue			Yellow	
Blue	Normally Acceptable	Specified land use is satisfactory, based upon the assumption that any buildings involved are of normal conventional construction, without any special noise insulation requirements.						
Green	Conditionally Acceptable	New construction or development should be undertaken only after a detailed analysis of the noise reduction requirements is made and needed noise insulation features are included in the design.						
Yellow	Normally Unacceptable	New construction or development should be discouraged. If new construction or development does proceed, a detailed analysis of the noise reduction requirement must be made and needed noise insulation features included in the design.						
Red	Clearly Unacceptable	New construction or development generally should not be undertaken.						

Source: OPR 1998; Imperial County General Plan 2008, as amended.

TABLE 4.11-2. PROJECT CONSISTENCY WITH APPLICABLE GENERAL PLAN NOISE POLICIES

General Plan Policies	Consistency with General Plan	Analysis
<p>1. <i>Acoustical Analysis of proposed projects.</i> The County shall require the analysis of proposed discretionary projects, which may generate excessive noise, or which may be impacted by existing excessive noise levels.</p>	Consistent	<p>Under existing conditions, the ambient noise environment is characterized as relatively quiet with peak noise levels influenced by agricultural operations. Given that the projects are not characterized as a sensitive land use, project facilities would be unaffected by existing noise levels. The project facilities would be constructed within areas zoned for agricultural use with noise levels up to 70 dBA identified as normally acceptable. Project operations are expected to produce noise levels that would not exceed County standards and, hence impacts are expected to be less than significant.</p> <p>This EIR provides an analysis of the potential short- and long-term noise impacts of the projects. As discussed, short-term and long-term noise levels were found to be less than significant.</p>
<p>2. <i>Noise/Land Use Compatibility.</i> Where acoustical analysis of a proposed project is required, the County shall identify and evaluate potential noise/land use conflicts that could result from the implementation of the project. Projects which may result in noise levels that exceed the "Normally Acceptable" criteria of the Noise/Land Use Compatibility Guidelines shall include mitigation measures to eliminate or reduce the adverse noise impacts to an acceptable level.</p>	Consistent	<p>Noise levels associated with project operations are unlikely to exceed noise limits for the A-2, A-2-R, and A-3 zones. See Section 4.11.1.2 for additional discussion.</p>
<p>4. <i>Interior Noise Environment.</i> Where acoustical analysis of a proposed project is required, the County shall identify and evaluate projects to ensure compliance to the California (Title 24) interior noise standards and the additional requirements of this Element.</p>	Consistent	<p>As described under General Plan Noise Policy 1, short-term and long-term noise impacts would be minimized through the implementation of the prescribed mitigation. Noise levels associated with project operations would be unlikely to exceed noise limits for the A-2, A-2-R, and A-3 zones.</p>
<p>5. <i>New Noise Generating projects.</i> The County shall identify and evaluate projects which have the potential to generate noise in excess of the Property Line Noise Limits. An acoustical analysis must be submitted which demonstrates the project's compliance.</p>	Consistent	<p>As described under General Plan Noise Policy 1, short-term and long-term noise impacts would be minimized through the implementation of the prescribed mitigation. Noise levels associated with project operations would be unlikely to exceed noise limits for the A-2, A-2-R, and A-3 zones.</p>
<p>6. <i>Projects Which Generate Off-site Traffic Noise.</i> The acoustical analysis shall identify and evaluate projects which will generate traffic and increase noise levels on off-site roadways. If the project site has the potential to cause a significant noise impact to sensitive receptors along those roadways, the acoustical analysis report shall consider noise reduction measures to reduce the impact to a level less than significant.</p>	Consistent	<p>As described in Chapter 3, the projects would involve a minimal number of operational related vehicle trips and therefore, is unlikely to produce any increase in traffic noise levels on local roadways.</p>

Source: Imperial County General Plan Noise Element.

The County of Imperial has established the following interior noise standards to be considered in acoustical analyses:

- The interior noise standard for detached single family dwellings shall be 45 dB CNEL; and
- The interior noise standard for schools, libraries, offices and other noise-sensitive areas where the occupancy is normally only in the day time, shall be 50 dB averaged over a one-hour period ($L_{eq}(1)$).

Construction Noise Standards

Construction noise, from a single piece of equipment or a combination of equipment, shall not exceed 75 dB L_{eq} when averaged over an eight (8) hour period, and measured at the nearest sensitive receptor. This standard assumes a construction period, relative to an individual receptor of days or weeks.

Construction equipment operation shall be limited to the hours of 7 AM to 7 PM, Monday through Friday, and 9 AM to 5 PM Saturday. No commercial construction operations are permitted on Sundays or holidays.

County of Imperial Noise Ordinance

Noise generating sources in Imperial County are regulated under the County of Imperial Codified Ordinances, Title 9, Division 7 (Noise Abatement and Control). Noise limits are established in Chapter 2 of this ordinance. Under Section 90702.00 of this rule, 70 dB is the normally acceptable limit for the Industrial, Manufacturing, Utilities, and Agricultural category of land use.

Imperial County Right-to-Farm Ordinance

In recognition of the role of agriculture in the county, the County of Imperial has adopted a “right-to-farm” ordinance (County of Imperial Codified Ordinances, Division 2, Title 6: Right to Farm). A “right-to-farm” ordinance creates a legal presumption that ongoing standard farming practices are not a nuisance to adjoining residences and requires a disclosure to land owners near agricultural land operations or areas zoned for agricultural purposes. The disclosure advises persons regarding potential discomfort and inconvenience that may occur from operating machinery as a result of conforming and accepted agricultural operations.

4.11.1.2 Existing Conditions

The predominant sources of noise in the project area includes vehicular traffic on local roads and highways and agricultural operations. Activities involving the use of heavy-duty equipment such as front-end loaders, forklifts, and diesel-powered trucks are common noise sources typically associated with agricultural uses. Noise typically associated with agricultural operations, including the use of heavy-duty equipment, can reach maximum levels of approximately 85 dBA at 50 feet (Caltrans 1998). With the soft surfaces characterizing the agricultural landscape, these noise levels attenuate to ~60 dBA at distances over 800 feet. Based on field observations of the project study areas, the existing noise environment is generally influenced by the noise produced from the following sources:

- Vehicle traffic along major roadways including Ferrell Road, George Road, Rockwood Road, Kubler Road, and State Route (SR) 98;
- Crop dusting operations based out of Johnson Brothers Private Airstrip; and
- Agricultural operations throughout the project area including the operation of heavy equipment and vehicles.

Based on the availability of a previously prepared noise study in conjunction with a recently approved Imperial Solar Energy Center South Project (Imperial County 2011), which is south and west of the

project area, the proximity of the measurements, and timing in which the data was collected (2010), the previously-acquired noise measurements are considered to be representative of existing conditions and appropriate for use in this EIR. Based on this circumstance, these measures were used to characterize ambient noise conditions for the project study areas.

The ambient noise levels within the project area are generally representative of a rural agricultural setting with quiet ambient noise levels of 43.3 dBA L_{eq} and periodic peak noise levels of 66.8 L_{max} from far-field agricultural operations (Imperial County 2011). These noise levels were slightly more elevated in closer proximity to the U.S./Mexico border with the increase attributed to the infrequent movement of U.S. Border Patrol units with ambient noise levels of 44.2 dBA L_{eq} and periodic peak noise levels of 78.8 L_{max} (Imperial County 2011). In addition to site-specific ambient noise sampling, the EIR prepared for the Imperial Solar Energy Center South Project included traffic modeling of the local roadway network. The existing (2010) traffic noise levels in the eastern portion of the Imperial Energy Center Solar South study area were established in terms of the CNEL metric by modeling the roadway for the current traffic and speed characteristics. In general, the 60 CNEL contour for all roadways within the project study areas, including SR 98, extends 70 feet or less from the roadway centerline (see Imperial Solar Energy Center South Final Environmental Impact Report/Environmental Assessment (EIR/EA), Section 3.8, page 3.8-9).

Sensitive Receptors

Although noise pollution can affect all segments of the population, certain groups and land uses are considered more sensitive to ambient noise levels than others, sensitivity being a function of noise exposure (in terms of both exposure duration and insulation from noise) and the types of activities involved. Children, the elderly, and the chronically or acutely ill are the most sensitive population groups..

Residential land uses are also generally more sensitive to noise than commercial and industrial land uses. Sensitive residential uses within and adjacent to the project area (within approximately 200 feet) are shown on Figure 4.3-1 (see Section 4.3, Air Quality), and include the following:

- Ferrell Solar Farm (1 onsite & 2 offsite) - The Corda residence and farm shop is located within the FSF project site off of Corda Road. The Kubler residence, farm shop and yard are located adjacent to the FSF project site (southwest corner of Kubler and Ferrell Roads) and another residence is located on the northeast corner of Kubler and Ferrell Roads.
- Rockwood Solar Farm (6 offsite) – One residence is located along the northern boundary of the RSF project site, two residences are located on the north side of Kubler Road (one at the intersection of George and Kubler Roads), and three residences are located at the intersection of Corda Road and SR 98 (two located south of SR-98).
- Iris Solar Farm (2 onsite) - Two residences are located within the ISF project site, along Ferrell Road. An old farm worker labor camp is located within the ISF project site along Weed Road, which is now used for a farming equipment staging area. No additional residences border the project site.
- Lyons Solar Farm. (2 offsite) - Two residences are located outside of the LSF project site (one at the intersection of Kubler and Rockwood Roads, and another across the Greeson Wash).

Some of the off site residences identified above are located within the site boundaries of previously approved solar projects including the Mount Signal and Calexico Solar Farm Projects; and the environmental effects on the off site residences have been previously evaluated in the respective EIR(s).

Groundborne Vibration

Groundborne vibration consists of rapidly fluctuating motions or waves, which are also measured in decibels. Construction activities, train operations, and street traffic are some of the most common external sources of vibration that can be perceptible inside structures. Differences in subsurface geologic conditions and distance from the source of vibration will result in different vibration levels characterized by

different frequencies and intensities. In all cases, vibration amplitudes will decrease with increasing distance. High frequency vibrations reduce much more rapidly than low frequencies, so that low frequencies tend to dominate the spectrum at large distances from the source. Discontinuities in the soil strata can also cause diffractions or channeling effects that affect the propagation of vibration over long distances.

Human response to vibration is difficult to quantify. Vibration can be felt or heard well below the levels that produce any damage to structures. The duration of the event has an effect on human response, as does frequency. Generally, as the duration and vibration frequency increase, the potential for adverse human response increases. While people have varying sensitivities to vibrations at different frequencies, in general they are most sensitive to low-frequency vibration. Vibration in buildings may be perceived as motion of building surfaces or rattling of windows, items on shelves, and pictures hanging on walls. Vibration of building components can also take the form of an audible low-frequency rumbling noise, which is referred to as groundborne noise.

Groundborne noise is usually only a problem when the originating vibration spectrum is dominated by frequencies in the upper end of the range (60 to 200 Hz), or when the structure and the source of vibration are connected by foundations or utilities, such as sewer and water pipes. To assess a project's vibration impacts, Caltrans has prepared a publication concerning vibration impact assessment, entitled the "Transportation and Construction-Induced Vibration Guidance Manual," which was prepared in 2004. The guidance manual uses peak particle velocity (PPV) to quantify vibration amplitude. Peak particle velocity is defined as the maximum instantaneous peak of the vibratory motion (Caltrans 2004). Table 4.11-3 identifies acceptable vibration limits for transportation and construction projects based on guidelines prepared by Caltrans.

Table 4.11-3. Typical Groundborne Vibration Thresholds

Structure and Condition	Transient Sources PPV at 25 feet (in/sec)	Continuous/Frequent Intermittent Sources PPV at 25 feet (in/sec)
Extremely fragile historic buildings, ruins, and ancient monuments	0.12	0.08
Fragile buildings	0.20	0.10
New residential structures with gypsum board walls/ceilings	1.00	0.50
Modern Industrial/commercial buildings	2.00	0.50
Strongly perceptible	0.90	0.10

Source: Caltrans 2004.

Notes: PPV = Peak particle velocity
In/sec = Inches per second

4.11.2 Impacts and Mitigation Measures

This section presents the significance criteria used for considering project impacts related to noise and vibration, the methodology employed for the evaluation, an impact evaluation, and mitigation requirements, if necessary.

4.11.2.1 Thresholds of Significance

Based on CEQA Guidelines Appendix G, project impacts related to noise and vibration would be considered significant if any of the following occurs:

- Expose persons to or generate noise levels in excess of standards established in the local general plan or noise ordinance, or applicable standards of other agencies;
- Expose persons to or generate excessive groundborne vibration or groundborne noise levels;

- Create a substantial permanent increase in ambient noise levels in the project vicinity above levels existing without the project;
- Create a substantial temporary or periodic increase in ambient noise levels in the project vicinity above levels existing without the project;
- For a project located within an airport land use plan or, where such a plan has not been adopted, within two miles of a public airport or public use airport, expose people residing or working in the project area to excessive noise levels; or
- For a project within the vicinity of a private airstrip, expose people residing or working in the project area to excessive noise levels.

4.11.2.2 Methodology

The significance of project-related noise impacts was determined by comparing estimated project-related noise levels, based on published literature, to existing noise levels within the project area as described in other recently-prepared environmental documents for other projects near the project area including the Imperial Solar Energy Center South EIR/EA (Imperial County 2011). For the purposes of analysis, an increase of at least 3 dBA is usually required before most people will perceive a change in noise levels, and an increase of 5 dBA is required before the change will be clearly noticeable. Based on the County's criteria, exposure of persons to or generation of noise levels in excess of standards established in the local general plan or noise ordinance would occur if:

1. Post-project noise levels will be greater than the “conditionally acceptable,” “normally acceptable,” or “clearly acceptable” noise levels as shown in Table 4.11-3 for Industrial, Manufacturing, Utilities and Agriculture Uses (or generally greater than 70 dB); or
2. Construction noise will be greater than 75 dB L_{eq} over an eight-hour period from the nearest sensitive receptor (see Figure 4.3-1).

Conceptual site plans provided in Figures 3.0-6 through 3.0-9 for the projects were used in considering distances from sensitive receptor locations. Given the agricultural landscape of the project study areas, noise attenuation was assumed to be 7.5 dBA for stationary sources and 4 dBA for line sources (e.g. vehicles). As provided in Chapter 3, Project Description, the projects would generate a low volume of daily vehicle trips under project operations and these trips would be distributed throughout the project study areas. Based on this circumstance and experience with projects of similar land use and development intensity, project-related increases traffic noise levels on off-site roadways were assumed to be less than 3.0 dBA as measured from residential receptor locations illustrated in Figure 4.3-1.

4.11.2.3 Impact Analysis

IMPACT 4.11-1 Temporary, Short-Term Exposure of Sensitive Receptors to Increased Equipment Noise from Project Construction.

The projects could expose persons to or generate noise levels in excess of applicable County standards.

Iris Cluster (FSF, RSF, ISF, and LSF) and Transmission Line

Construction of the projects would occur in rural portions of southern Imperial County. Over the entire span of the combined 1,400~~4~~,422-acre area, which comprises the four project sites, there are approximately 13 rural residences that would be located within 100 to 200 feet of project construction. Two residences are located outside of the LSF site boundary, but the distance from the site boundary to the residences exceeds 500 feet. Construction activities would generally involve grading, earth movement, stockpiling, steel work, and truck hauling. Similar activities would occur upon site decommissioning. These activities would generate temporary and intermittent noise at and near the project sites. Noise levels would fluctuate depending on the particular type, number, and duration of use

of various pieces of construction equipment. In addition, construction-related material haul trips would raise ambient noise levels along haul routes depending on the number of haul trips and the types of vehicles used. These activities would be more pronounced at the operation and maintenance (O&M) and substation sites where construction activities would occur for an extended time period. Table 4.11-4 shows typical noise levels produced by various types of construction equipment at a distance of 50 feet.

In addition to actual solar array grid installation, staging areas would be located at various points throughout the project area and directed out of a more centralized location, such as the O&M sites (see Figure 3.0-3 through 3.0-6). These areas would be used to store PV/CPV solar panels, equipment, and other construction related material. In some cases, staging areas would be used for the duration of project construction. In other cases, the area would be moved to another location within the project sites to minimize the hauling distances and avoid disrupting any one area for an extended period of time. Staging areas could be noticeable sources of noise, particularly if equipment is accessed and moved during evening hours when individuals are more sensitive to intrusive noise.

Table 4.11-4. Typical Noise Levels for Construction Equipment

Equipment	Typical Noise Levels (dBA, at 50 feet)	Equipment	Typical Noise Levels (dBA, at 50 feet)
Front loaders	85	Forklifts	76-82
Backhoes, excavators	80-85	Pumps	76
Tractors, dozers	83-89	Generators	81
Graders, scrapers	85-89	Compressors	83
Trucks	88	Pneumatic tools	85
Concrete pumps, mixers	82-85	Jack hammers, rock drills	98
Cranes (movable)	83	Pavers	89
Cranes (derrick)	88	Compactors	82
Pipelayers	83-88	Drill rigs	70-85

Source: Adapted from U.S. Department of Transportation, Federal Transit Administration, Noise and Vibration Impact Assessment Guidelines 2006.

Based on the noise levels provided in Table 4.11-4 and assuming conservative rates of attenuation, noise levels generated during project construction could range from 74 to 79 dBA at the nearest receptor locations (e.g., 100 feet) depending on the types of equipment in operation. Additionally, back-up beepers (in order to be discernible and protect construction worker safety as required by Occupational Safety and Health Administration (OSHA) (29 CFR 1926.601 and 29 CFR 1926.602)) associated with trucks and equipment used for material loading and unloading at the staging areas would generate significantly increased noise levels over the ambient noise environment. The Noise Element of the Imperial County General Plan identifies sensitive receptors as areas of habitation and may also be non-human species (i.e., sensitive bird species). There are 13 residences located within or in close proximity to the project sites and in the vicinity. Three residences are located within the boundaries of the FSF and ISF project sites, as described above and shown on Figure 4.3-1, Residence Locations. As shown, noise associated with construction equipment could exceed the 75 dB L_{eq} threshold identified in the County of Imperial Noise Element; thus the noise could disturb potential adjacent sensitive receptors (areas of habitation) per the requirements by the County of Imperial.

In addition and as discussed in Chapter 4.4, Biological Resources of this EIR, burrowing owls and other sensitive birds were observed within the project area. Chapter 4.4, Biological Resources provides a detailed discussion on the potential impacts to burrowing owls and other sensitive bird species (non-human sensitive receptor) and mitigation measures that will avoid, minimize, or mitigate potential impacts to these species.

Because existing daytime noise levels in the vicinity of the project construction are generally less than 50 to 60 dBA, daytime construction work associated with the projects would significantly affect the noise environment of residences in proximity to construction activities by increasing ambient noise levels by five

dBA or more and peak noise levels of 84 to 89 dBA. While construction activities would occur when a majority of people are at work, retired persons, people who work at home, and people caring for their children in their homes could be significantly affected, although temporarily, by noise when construction activities are occurring in the immediate vicinity. This temporary and short-term impact is considered a **significant impact** in the absence of mitigation. However, the implementation of Mitigation Measures 4.11-1a through 4.11-1e would reduce these levels to **less than significant**.

Mitigation Measure(s)

The following mitigation measures are required for the FSF, RSF, ISF, LSF, and transmission line.

- 4.11-1a Limit Construction Hours.** Construction and decommissioning activities shall be limited to daylight hours between 7 AM and 7 PM Monday through Friday, and 9 AM and 5 PM on Saturday for those construction areas that are located within 2,500 feet of noise-sensitive receptors. No construction shall be allowed on Sundays or holidays.
- 4.11-1b Minimize Noise from Construction Equipment and Staging.** Construction equipment noise shall be minimized during project construction and decommissioning by muffling and shielding intakes and exhaust on construction equipment (per the manufacturer's specifications) and by shrouding or shielding impact tools, where used. The project applicant's construction specifications shall also require that the contractor select staging areas as far as feasibly possible from sensitive receptors. All contractor specifications shall include a requirement that equipment located within 2,500 feet of noise-sensitive receptors shall be equipped with noise reducing engine housings or other noise reducing technology such that noise levels are no more 85 dBA at 50 feet. If necessary the line of sight between the equipment and nearby sensitive receptors shall be blocked by portable acoustic barriers and/or shields to reduce noise levels.
- 4.11-1c Maximize the Use of Noise Barriers.** Construction and decommissioning contractors shall locate fixed construction equipment (such as compressors and generators) as far as possible from nearby residences. If feasible, noise barriers shall be used at the construction site and staging area. Temporary walls, stockpiles of excavated materials, or moveable sound barrier curtains would be appropriate in instances where construction noise would exceed 85 dBA and occur within less than 200 feet from a sensitive receptor. The final selection of noise barriers shall be subject to the project applicant's approval and shall provide a minimum 5 dBA reduction in construction noise levels, where noise levels would exceed 85 dBA without the barrier.
- 4.11-1d Prohibit Non-Essential Noise Sources During Construction.** No amplified sources (e.g., stereo "boom boxes") shall be used in the vicinity of residences during project construction or decommissioning.
- 4.11-1e Provide a Mechanism for Filing Noise Complaints.** The project applicant shall provide a mechanism for residents, businesses, and agencies to register complaints with the County if construction noise levels are overly intrusive or construction occurs outside the required hours.

Significance After Mitigation

Implementation of the above mitigation measures would reduce construction noise, so that construction and decommissioning-related noise levels would not exceed the Imperial County standards regarding construction noise. Mitigation would reduce temporary, short-term construction and decommissioning impacts-related impacts to a **less than significant** level.

IMPACT
4.11-2**Exposure to and/or Generation of Groundborne Vibration.**

The projects would not expose persons to or generate excessive groundborne vibration or groundborne noise levels.

Iris Cluster (FSF, RSF, ISF, and LSF) and Transmission Line

Construction and site decommissioning activities associated with the projects would result in groundborne vibration, with the primary sources including solar array installation, grading activities, and other construction vehicle movements. In addressing the range of potential issues associated with ground vibration, there are generally two forms of impacts that should be addressed: (1) annoyance to individuals or the community; and (2) damage to buildings. Vibration from typical construction activities is typically below the threshold of perception when the activity is more than about 50 feet from the receiver. However, given that construction activities would not encroach within 100 feet of existing residential structures, the level of vibration impact at these receptors would be **less than significant**.

In relation to the potential for structural damage at adjacent residential and agricultural structures, PPV is the maximum instantaneous positive or negative peak of the vibration signal, measured as a distance per time (such as millimeters or inches per second). The PPV measurement has been used historically to evaluate shock-wave type vibrations from actions like blasting, pile driving, and mining activities, and their relationship to building damage.

As provided in Table 4.11-3, the level of potential impact resulting from project construction is generally contingent on the structural composition of the buildings potentially affected. As shown in Table 4.11-3, new residential structures with gypsum board walls/ceilings have a PPV threshold of 1.0 inches per second (in/sec), respectively and would be the types of structures most likely to be impacted by project construction activities. No historical structures are presented within or adjacent to the project study areas. Given that construction activities would employ the use of equipment similar to those identified in Table 4.11-5, would not involve the use of blasting, and would be situated 100 feet or more from existing structures, project construction is unlikely to generate vibration levels in excess of the thresholds identified in Table 4.11-3. For this reason, groundborne vibration-related impacts during construction and site decommissioning are expected to be **less than significant**.

TABLE 4.11-5. CONSTRUCTION EQUIPMENT VIBRATION LEVELS

Equipment PPV at 25 feet (in/sec)	Equipment PPV at 25 feet (in/sec)
Blasting	1.13
Vibratory roller	0.210
Large bulldozer	0.089
Caisson drilling	0.089
Loaded trucks	0.076
Jackhammer	0.035
Small bulldozer	0.003

Source: Federal Transit Administration, Transit Noise and Vibration Impact Assessment, May 2006.

Mitigation Measure(s)

No mitigation measures are required.

IMPACT *Permanent Increase in Ambient Noise Levels.*

4.11-3

The projects could create a substantial permanent increase in ambient noise levels in the vicinity of new O&M and substation facilities.

FSF

As described in Section 3.1.1.2, the ambient noise environment within the project area ranges from 43 to 66 dBA with peak noise measurements of up to 78 dBA (Imperial County 2011). The principle long-term, operational noise impacts resulting from the projects would include light duty vehicle traffic for security patrols, maintenance operations, including solar panel washing, central operations at O&M facilities, including stationary mechanical equipment (e.g., HVAC), and low level of noise from high voltage transmission lines and transformers. Additionally, based on measurements provided by the project applicant, noise levels associated with a tracker mounting system were measured at 45 dBA at 100 feet. The on-site water storage tanks located at each of the O&M buildings would require associated pumping and would operate intermittently. The level of noise generated by these combined sources would depend on: characteristics of the noise source, number of noise sources clustered together, type and effectiveness of building enclosure, and operational characteristics.

Operation of the O&M facilities, substations, and electrical distribution facilities would result in a minor increase in the use of motor vehicles, primarily associated with employees traveling to and from these facilities and routine maintenance and inspection activities. It is expected that no more than 24 staff personnel would be on site at any one time for typical operation and maintenance of these facilities, most during typical working hours, 7 AM to 5 PM. Assuming an average of two trips per employee, operation of the proposed facilities would result in approximately 48 one-way daily employee trips. Additionally, these trips would be distributed through the roadway network. Due to the relatively low volume of project-generated traffic, operation of the proposed facilities would not result in noticeable changes in the traffic noise along area roadways in relation to existing and projected roadway traffic volumes. As a result, long-term increases in traffic noise levels would be **less than significant**.

The projects would be required to comply with the County of Imperial Codified Ordinances Division 7 Noise Abatement and Control. This ordinance governs fixed operational noise within the project study areas. The 1-hour average sound level limit for the A-2, A-2-R, and A-3 zones is 75 dBA and noise levels up to 70 dBA L_{dn} are identified as normally acceptable (see Table 4.11-1). The noise generated during these collective operations would be required to comply with the noise standards contained in the County's Noise Ordinance. The noise associated with O&M facilities is does not represent a significant noise source, and would involve less intensive activities and operation of equipment as compared to existing agricultural operations in the area. The impact would be **less than significant**.

RSF, ISF, and LSF

Development of the project facilities at these site locations would entail the placement and operation of the same facilities as described above. However, unlike the FSF site, these facilities would result in the placement of the O&M and substation facilities at distances of greater than 1,000 feet from the nearest residential receptor. Although portions of these project sites are located in proximity to existing residences, the major noise generating operations for these projects would be located a sufficient distance to where any increase in ambient noise levels would be unnoticeable at the nearest sensitive receptor. Based on these considerations, long term impacts to the ambient noise environment at these site locations would be **less than significant**.

Transmission Line

Operation of the transmission lines would **not impact** adjacent receptors.

Mitigation Measure(s)

No mitigation measures are required.

IMPACT *Airport Noise.*

4.11-4 *The projects would not result in the exposure of people residing or working in the project study areas to excessive noise levels from public and private airport operations.*

Iris Cluster (FSF, RSF, ISF, and LSF) and Transmission Line

The projects would not involve the construction of sensitive land uses. No O&M facilities would be constructed within two miles of a public airport and, therefore, would not expose people to excessive airport noise levels. The project facilities would be located within proximity to the Johnson Brothers private airstrip; however, based on the frequency and limited number of planes using this private facility, noise levels are considered **less than significant**.

Mitigation Measure(s)

No mitigation measures are required.

4.11.3 Decommissioning/Restoration and Residual Impacts

Decommissioning/Restoration

Decommissioning activities would result in similar activities that are involved during construction such as grading, earth movement, stockpiling, steel work, and truck hauling. These activities would generate temporary and intermittent noise. Noise levels would fluctuate depending on the particular type, number, and duration of use of various pieces of construction equipment. As a result, these impacts are considered a **significant impact** and require the implementation of mitigation measures. Mitigation Measures 4.11-1a through 4.11-1d, identified above under Impact 4.11-1, would address any noise impacts associated with decommissioning activities and upon implementation, reduce these impacts to levels **less than significant**.

Given that decommissioning activities would employ the use of equipment similar to those identified in Table 4.11-5, would not involve the use of blasting, and would be situated 100 feet or more from existing structures, decommissioning is unlikely to generate vibration levels in excess of the thresholds identified in Table 4.11-3. For this reason, groundborne vibration-related impacts during site decommissioning are expected to be **less than significant**.

Residual

After implementation of feasible mitigation, construction and decommissioning noise impacts would be less than significant. The operational noise impacts associated with the projects in proximity to existing residential receptors would be mitigated to a less than significant level through the incorporation of buffering requirements for O&M, transformer facilities, and storage tank pumps. The projects are situated at a sufficient distance where the effects of construction related vibration would **not impact** adjacent receptors.